



KÖR FLANŞLAR PN10 BLIND FLANGES PN10

EN 1092-1 DIN 2527
Tip 05 /

| BORU PIPE | FLANŞ / FLANGE | | | ALIN ÇIKTIŞI / RAISED FACE | | DELİKLER / DRILLINGS | | | AĞIRLIK WEIGHT |
|--------------|----------------|----|------|----------------------------|----------------|----------------------|-----|------------------|-------------------|
| | DN | D | b | k | d ₄ | f | n | saplama screw | d ₂ |
| 10 | 90 | 16 | 60 | 40 | 2 | 4 | M12 | 14 | 0,63 |
| 15 | 95 | 16 | 65 | 45 | 2 | 4 | M12 | 14 | 0,72 |
| 20 | 105 | 18 | 75 | 58 | 2 | 4 | M12 | 14 | 1,01 |
| 25 | 115 | 18 | 85 | 68 | 2 | 4 | M12 | 14 | 1,23 |
| 32 | 140 | 18 | 100 | 78 | 2 | 4 | M16 | 18 | 1,8 |
| 40 | 150 | 18 | 110 | 88 | 2 | 4 | M16 | 18 | 2,09 |
| 50 | 165 | 18 | 125 | 102 | 2 | 4 | M16 | 18 | 2,88 |
| 65 | 185 | 18 | 145 | 122 | 2 | 8 | M16 | 18 | 3,66 |
| 80 | 200 | 20 | 160 | 138 | 2 | 8 | M16 | 18 | 4,77 |
| 100 | 220 | 20 | 180 | 158 | 2 | 8 | M16 | 18 | 5,65 |
| 125 | 250 | 22 | 210 | 188 | 2 | 8 | M16 | 18 | 8,42 |
| 150 | 285 | 22 | 240 | 212 | 2 | 8 | M20 | 22 | 10,4 |
| 200 | 340 | 24 | 295 | 268 | 2 | 8 | M20 | 22 | 16,5 |
| 250 | 395 | 26 | 350 | 320 | 2 | 12 | M20 | 22 | 24 |
| 300 | 445 | 26 | 400 | 370 | 2 | 12 | M20 | 22 | 30,9 |
| 350 | 505 | 26 | 460 | 430 | 2 | 16 | M20 | 22 | 40,6 |
| 400 | 565 | 26 | 515 | 482 | 2 | 16 | M24 | 26 | 49,4 |
| 450 | 615 | 28 | 565 | 532 | 2 | 20 | M24 | 26 | 63 |
| 500 | 670 | 28 | 620 | 585 | 2 | 20 | M24 | 26 | 75 |
| 600 | 780 | 34 | 725 | 685 | 2 | 20 | M27 | 30 | 125 |
| 700 | 895 | 38 | 840 | 800 | 2 | 24 | M27 | 30 | 185 |
| 800 | 1015 | 42 | 950 | 905 | 2 | 24 | M30 | 33 | 260 |
| 900 | 1115 | 46 | 1050 | 1005 | 2 | 28 | M30 | 33 | 345 |
| 1000 | 1230 | 52 | 1160 | 1110 | 2 | 28 | M33 | 36 | 475 |
| 1200 | 1455 | 60 | 1380 | 1330 | 2 | 32 | M36 | 39 | 780 |

Ölçüler mm dir. / Dimensions are in mm.