



KÖR FLANŞLAR PN16

BLIND FLANGES PN16

EN 1092-1 DIN 2527
Tip 05 /

BORU PIPE	FLANŞ / FLANGE			ALIN ÇIKTISI / RAISED FACE		DELİKLER / DRILLINGS			AĞIRLIK WEIGHT
	DN	D	b	k	d ₄	f	n	saplama screw	d ₂
10	90	16	60	40	2	4	M12	14	0,63
15	95	16	65	45	2	4	M12	14	0,72
20	105	18	75	58	2	4	M12	14	1,01
25	115	18	85	68	2	4	M12	14	1,23
32	140	18	100	78	2	4	M16	18	1,8
40	150	18	110	88	2	4	M16	18	2,09
50	165	18	125	102	2	4	M16	18	2,88
.65	185	18	145	122	2	8	M16	18	3,66
80	200	20	160	138	2	8	M16	18	4,77
100	220	20	180	158	2	8	M16	18	5,65
125	250	22	210	188	2	8	M16	18	8,42
150	285	22	240	212	2	8	M20	22	10,4
200	340	24	295	268	2	12	M20	22	16,1
250	405	26	355	320	2	12	M24	26	24,9
300	460	28	410	378	2	12	M24	26	35,1
350	520	30	470	438	2	16	M24	26	47,8
400	580	32	525	490	2	16	M27	30	63,5
450	640	40	585	550	2	20	M27	30	75
500	715	44	650	610	2	20	M30	33	102
600	840	54	770	725	2	20	M33	36	149,7
700	910	48	840	795	2	24	M33	36	173,7
800	1025	52	950	900	2	24	M36	39	235,5
900	1125	58	1050	1000	2	28	M36	39	298,8
1000	1255	64	1170	1115	2	28	M39	42	390,7
1200	1485	76	1390	1330	2	32	M45	48	624,8

Ölçüler mm dir. / Dimensions are in mm.